

























- [4] S.E.Selke and I. Wichman, "Wood fiber/polyolefin composites. Composites": Part A: Applied Science and Manufacturing, 35, 321-326, 2004.
- [5] M. Kaci, S. Cimmino, C. silvestre, D. Duraccio, A. Benhamida and L. Zaidi, "Ethylene butyl acrylate glycidylmethacrylate terpolymer as an interfacial agent for isotactic polypropylene/wood flour composites". Macromolecular Materials and engineering, 291, 869-876, 2006.
- [6] S.N. Walford, "Sugarcane bagasse: How easy is it to measure its constituents" ? Proceedings South Africa Sugar Technology Association , 81: 266 – 273, 2008.
- [7] S.Y. Ding and M.E. Himmel, The maize primary cell wall microfibril: a new model derived from direct visualisation Journal Agric Food Chemistry, 54: 597-606, 2006.
- [8] S.E. Jacobsen and C.E Wyman, Cellulose and hemicelluloses hydrolysis models for application to current and novel pretreatment processes". Applied Biochemistry Biotechnology, 84-86: 81-96, 2000.
- [9] A.K. Mohanty, M. Misra and L.T. Drzal, Evaluation of interphase properties in fiber reinforced polymer composite using contact resonance force microscopy". Composite Interfaces, 8: 313, 2001.
- [10] B. Netral, T. Sabu, K.D. Chapal and A. Rameshwa, "Analysis of morphology and mechanical behaviors of bamboo flour reinforced polypropylene composites". Nepal Journal of Science and Technology 13(1): 95-100, 2012.
- [11] M. Tajvidi and G. Ebrahimi, "Water uptake and mechanical characteristics of natural-polypropylene composites". Journal of Applied Polymer Science, 88: 941-946, 2003.
- [12] M. E. Malaini, M. Mahroq, A. Lafresne, "Magnoculosic flour from cladodes of opuntia ficus-indica reinforced polypropylene composites". Macromolecular Materials and Engineering, 289: 859-863, 2004.
- [13] Q. Li and L. M. Matuana, Surface of cellulosic material modified with functionalized polyethylene coupling agent. Journal of Applied Polymer Science, 88: 278-284, 2003.
- [14] A.G. Supri and B.Y Lim, "Effect of treated and untreated filler loading on the mechanical, morphological, and water absorption properties of water hyacinth fibers low density polyethylene composites". Journal of Physical Science, 20(2): 85-96, 2009.
- [15] A.I. Khuri and J.A. Cornell, Dekker M. Response surfaces: design and analysis. New York: Dekker; 1987.
- [16] K. Kuchi, "Hopped delay for multiply process power control and handover procedure and optimization", Irving USA, Wiley, 2000.