ON THE STABILIY AND ASYMPTOTIC STABILITY OF THE PERIODIC SOLUTION OF A LIENARD EQUATION

¹E.O.Eze, ²U.E. Obasi and ³S.I Ezeh

^{1,2} Department of Mathematics, Michael Okpara University of Agriculture, Umudike, Umuahia. Abia state Nigeria.

Email:obinwanneeze@gmail.com, sirurchobasi@gmail.com and ijeoma4mary@yahoo.com

Corresponding author: obinwanneeze@gmail.com, 08033254972

Abstract

This paper propose a qualitative approach to the periodic solution of a Lienard equation using Lyapunov direct method and Cartwright method to achieve asymptotic stability and hence stability of the solution. Futhermore, Mathcad was applied to demonstrate the numerical behavior of the solution which improves and extends some results in literature.

Keywords: Cartwright Method, Asymptotic Stability, Lyapunov Direct Method, Lienard Equation, Stability

Mathematics Subject Classification (2010): 34B15, 34C15, 34C25, 34K13

1. Introduction

Consider a second order differential equation of the Lienard type

$$\ddot{x} + c\dot{x} + ax = h(t) \tag{1.1}$$

with boundary conditions

$$x(0) = x(2\pi)$$
$$\dot{x}(0) = \dot{x}(2\pi)$$

where h(t) is one of the following *T* -periodic functions: h(t) = ksin(wt), h(t) = kcos(wt)and h(t) = e(t). \ddot{x} is the second derivative with respect to time and *c*, *a* are real constants. Lienard equation named after French physicist Alfred-Marie Lienard is a second order differential equation used to model oscillating circuits [1]. The equation is intensely studied during the development of radio and vaccum tube technology. In the presence of a linear restoring and non-linear damping, Lienard equation describes the dynamics of a system with one degree of freedom. These can be seen in the generalized Lienard equation

$$x''(t) + f(x)x' + x = h(t)$$
(1.2)

where f(x) and g(x) are continuously differentiable on \mathbb{R} . If the function f has the property f(x) < 0 for small |x|, f(x) > 0 for large |x| ie. If for small amplitudes the system absorbs energy and for large amplitude dissipation occurs, then in the system one can expect self-existing oscillations [2]. An important special case of the Lienard equation is the Vander Pol equation which is used to model the periodic firing of nerve cells driven by a constant current [3]. Due to importance of Lienard equation in ecological, biological as well as mechanical systems, many researches have used different techniques to obtain solutions of Lienard equation with resounding results. For instance see [4]-[7]. On the asymptotic stability of Lienard equation see [8]-[13] and the reference therein.

This paper is motivated by studying [14] and [15]. The objective of this paper therefore is to investigate the stability and asymptotic stability of the equilibrium point formed by a Lienard equation using Lyapunov direct method. The result presented in this paper in an improvement of the result announced in [16].

This paper is divided into four sections. In section 2, we present some preliminary results and in three, we presented the results and discussion, demonstrating the numerical solution of the Lienard equation using MATHCAD software and in five, we concluded.

2. Preliminaries

Definition 2.1 Consider the system

$$\dot{x} = f(t, x), \qquad x(t_0) = x_0$$
 (1.3)

where $x: I \to \mathbb{R}^n$ and $f: D \subseteq I \times \mathbb{R}^n \to \mathbb{R}^n$ are maps, *I* is an interval of real line, *D* is an open subset of $\mathbb{R} \times \mathbb{R}^n$; $n \ge 1$ and *f* is such that (1.3) has a unique solution.

(a) Let z(t) be a solution of (1.3). The solution z(t) of (1.3) is said to be stable (in the sense of Lyapunov) if given $\varepsilon > 0$ there exist $\delta = \delta(t_0, \varepsilon) > 0$ such that all solution x(t) of (1.3) satisfying $||x_0 - z_0|| < \delta$ implies $||x(t) - z(t)|| < \varepsilon$ for $t \ge t_0$

(b) If $\delta = \delta(\varepsilon)$ only we say that the stability is uniform in it does not depend on time at any time the solution holds.

(c) The trivial solution x = 0 of (1.3) is said to be asymptotically stable if it is both stable and such that $\lim_{t \to \infty} ||x(t)|| = 0$.

(d) The trivial solution x = 0 of (1.3) is said to be uniformly asymptotically stable if it is both uniformly stable and $\lim_{t \to \infty} ||x(t)|| = 0$ holds.

(e) The trivial solution x = 0 of (1.3) is said to be unstable if for any $\varepsilon > 0$ there exist a $\delta = \delta(-,\varepsilon) > 0$ such that all solutions x(t) of (1.3) satisfying $||x_0|| < \delta$ implies $||x(0)|| > \varepsilon$ for $t_1 > t_0$.

Remark: Lyapunov stability means that an arbitrary narrow ε –neighbourhood of the solution x(t) contain all the solutions of (1.3) which sufficiently close to $z(t_0) = z_0$ at the initial moment t_0 .

Theorem 2.2 Consider the scalar equation

$$\dot{x} = f(x); \quad x \in \mathbb{R}^n, \quad f(0) = 0$$
(1.4)

where f is sufficiently smooth. Assume that

(i)
$$f \in C^1$$

(*ii*) Then there exist C^1 function $v: \mathbb{R}^n \to \mathbb{R}$ such that v(x) > 0 for every x and v(x) = 0 if

$$x = 0$$

(*iii*) Along the solution paths of the equation (1.4) $\dot{v} \leq 0$, then the solution x = 0 of equation (1.4) is stable in the sense of Lyapunov.

Theorem 2.3 Assume that

(i) $f \in C^1$

(*ii*) Then there exist C^1 function $v: \mathbb{R}^n \to \mathbb{R}$ such that v(x) > 0 for every x and v(x) = 0 if

$$x = 0$$

(*iii*) Along the solution paths of the equation (1.4) $\dot{v} < 0$, if $x \neq 0$ and $\dot{v} = 0$ ie \dot{v} is negative definite then the solution x = 0 of equation (1.4) is asymptotically stable in the sense of Lyapunov.

3. Results and Discussion

3.1 Stability Analysis by Lyapunov Direct Method.

Lyapunov direct method is an importance concept in stability theory because it defines the behavior of solutions of some nonlinear differential equation and invariably helps to determine the stability of many differential equation [16]. To establish the stability of Lienard equation, it requires that h(t) = 0 which means that

$$\ddot{x} + c\dot{x} + ax = 0$$
(1.5)
Let $x = x_1$, $\dot{x}_1 = x_2$, $\dot{x}_2 = -cx_2 - ax_1$
The equivalent system is given by
 $\dot{x}_1 = x_2$
 $\dot{x}_2 = -cx_2 - ax_1$

Let us consider the function $v: \mathbb{R}^2 \to \mathbb{R}$ is given by

$$v = \frac{1}{2}x_2^2 + H(x_1) \tag{1.6}$$

where $H(x_1) = \int_0^{x_1} h(s) ds$

Clearly v as defined in (1.6) is positive semi-definite. The time derivative \dot{v} along the solution paths of the equation (1.5) is

$$\dot{\nu} = x_2 \dot{x}_2 + h(x_1) \dot{x}_1 \tag{1.7}$$

where $h(x_1) = a(x_1)$

$$\dot{v} = x_2(-cx_2 - ax_1) + (ax_1)\dot{x}_1$$

$$= -cx_2^2 - ax_1x_2 + ax_1x_2$$

= $-cx_2^2$ (1.8)

which is negative definite. Therefore by Lyapunov theorem, the system is asymptotically stable and hence stable in the sense of Lyapunov when h(t) = 0.

3.2 Stability Analysis by Cartwright Method.

Lyapunov functions are vital in determining stability, instability, boundedness and periodicity of ordinary differential. We adopt the method of construction of Lyapunov function used in [17] and extend it to second order differential equation of Lienard type in equation (1.5). The procedure is as follows:

First, we transform equation (1.5) into a system given by

$$\dot{x}_1 = x_2$$
 (1.9)
 $\dot{x}_2 = -cx_2 - ax_1$ (1.10)

Writing compactly, we have

$$\dot{X} = AX \tag{1.11}$$

Where
$$A = \begin{bmatrix} 0 & 1 \\ -a & -c \end{bmatrix}$$
 and $X = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ (1.12)

The method discussed here is based on the fact that the matrix A defined in equation (1.12) has all its eigenvalues with negative real parts. Then from the general theory which corresponds to any positive quadratic form U(x), there exists another positive definite quadratic form V(x) such that

$$V = -U \tag{1.13}$$

We choose the most general quadratic form of order two and pick the coefficient in the quadratic form to satisfy equation (1.13) along the solution paths of equation (1.10). Let *V* be defined by

International Journal of Scientific & Engineering Research Volume 10, Issue 2, February-2019 ISSN 2229-5518

$$2V = Ax_1^2 + Bx_2^2 + 2Kx_1x_2 \tag{1.14}$$

Differentiating equation (1.14) gives

$$\dot{V} = Ax_1\dot{x}_1 + Bx_2\dot{x}_2 + K(\dot{x}_1x_2 + \dot{x}_2x_1)$$
(1.15)

$$= Ax_1x_2 + B(-cx_2 - ax_1)x_2 + Kx_2^2 + Kx_1(-cx_2 - ax_1)$$
(1.15)

$$= Ax_1x_2 - Bcx_2^2 - Bax_1x_2 + Kx_2^2 - Kcx_1x_2 - Kax_1^2$$
(1.16)

Simplifying the coefficients we have

$$\dot{V} = (A - Ba - Kc)x_1x_2 + (K - Bc)x_2^2 - Kax_1^2$$
(1.17)

To make \dot{V} negative definite, we adapt the Cartwright method (1956) by equating the coefficient of mixed variable to zero and the coefficients of x_1^2 and x_2^2 to any positive constant (say δ) we have

$$A - Ba - Kc = 0 \tag{1.18}$$

$$K - Bc = \delta \tag{1.19}$$

$$-Ka = \delta \tag{1.20}$$

From equation (1.20)

$$K = -\frac{\delta}{a} \tag{1.21}$$

Then substituting the value of K into equation (1.19) we obtain

$$B = -\frac{\delta(a+1)}{ca} \tag{1.22}$$

Substituting for *K* and *B* in (1.18) we have

International Journal of Scientific & Engineering Research Volume 10, Issue 2, February-2019 ISSN 2229-5518

$$A = -\frac{\delta}{ca} [a + a^2 - c^2]$$
(1.23)

The Lyapunov function is gotten by substituting for the values of the constant A, B, K in equation (1.14) which gives

$$2V = \frac{\delta}{ca} \left[x_1^2 (a + a^2 - c^2) - x_2^2 (1 + a) - 2cx_1 x_2 \right]$$
(1.24)


$$V = \frac{\delta}{2ca} \left[x_1^2 (a + a^2 - c^2) - x_2^2 (1 + a) - 2cx_1 x_2 \right]$$

For *V* to be positive definite $\frac{\delta}{ca} = 1$ which gives

$$V(x) = \frac{1}{2} [x_1^2(a + a^2 - c^2) - x_2^2(1 + a) - 2cx_1x_2] > 0$$

Hence at the equilibrium point, the system is asymptotically stable since $\dot{V} < 0$

3.3. Numerical Solution of Lienard equation






Figure 1: Trajectory profile of Lienard equation $\begin{array}{c}
x_2 \\
x_2 \\
x_1 \\
a = 0.6 \\
c = 0.5
\end{array}$

Figure 2: Phase portrait of Lienard equation when a = 0.6 and c = 0.5




Figure 4: Phase portrait for Lienard equation depicting asymptotic stability of solution as a spiral sink.




Figure 6: Phase portrait of Lienard equation when a = 0.2 and c = 0.03




Figure 8: Phase portrait for Lienard equation when a = 0.5 and c = 0.6

4. Conclusion

Lyapunov direct method and Cartwright method has proved to be a useful tool for the analysis of a Lienard type equation. Through some exploits on the first order equivalent systems, we established asymptotic stability and hence the stability of the equation using the two methods. This shows that the equilibrium point of Lienard equation is highly stable. The MATHCAD software has been shown to be effective in supporting the methods used in demonstrating the behavior of the Lienard equation. Using MATHCAD, we obtained the phase portraits and trajectory for different values of *a* and *c*. The application of this work is found in mechanics where the oscillatory motion of the wheel of a moving vehicle is always directed toward a fixed point. However the disadvantage is that finding a Lyapunov function is more of an art than a science which makes this work open for further research.

References

[1] Lienard A. (1928), Etude des oscillations entretenus, Revue generale de l'electricite, 23:901-912.

[2] Andronov A.A, Vitt A.A and Ichalkin A.E (1987), Theory of oscillators, Dover reprint.

 [3] Pilipenko A.M and Biryukov V.N (2013), Investigation of modern numerical analysis methods of self oscillatory circuit efficiency, *Journal of Radio Electronics* 8, UDC 621.372, 532.59

[4] Nowak W., Geiyer D. and Tuhin D. (2016), Absolute stability analysis using the Lienard equation: A study derived from control of fuel cell ultra-capacitor hybrids. *Journal of Dynamical System*, **138**(3): 1-10.

[5] Baker J.W (1974), Stability properties of a second order damped and forced nonlinear differential equation. *Journal on Applied Mathematics*, **27**(1): 159-166.

[6] Tunc C. (2013), Stability to vector Lienard equation with constant deviating argument. *Journal of Nonlinear Dynamics*, **73**(3): 1245-1251.

[7] Heidel J.W (1972), A Liapunov function for a generalized Lienard equation. *Journal of Mathematical Analysis and Application*, **39**: 192-197.

[8] Kato J. (1986), On a boundedness condition for solutions of a generalized Lienard equation. *Journal of Differential equation*, **65**(2): 269-286.

[9] Burton T.A and Townsend C.G (1971), Stability regions of the force Lienard equation. *Journal of London Mathematical Society*, **52**(3): 393-402.

[10] Jiang J.F (1997), The global stability of a class of second order differential equation. *Journal of nonlinear analysis*, **28**: 855-870.

[11] Sugie J., Chen D.L and Matsunaga H. (1998), On global asymptotic stability of systems of Lienard type. *Journal of Mathematical Analysis and Application*, **219**: 140-164.

[12] Heidel J.W (1970), Global asymptotic stability of a generalized Lienard equation. *Journal of Applied Mathematics*, **19**(3): 629-636.

[13] Chunji L. (2001), On global asymptotic stability of generalized Lienard equation. *Trends in Mathematics*, **4**(2): 127-131.

[14] Zhou O. and Long F. (2007), Existence and Uniqueness of periodic solutions for a kind of Lienard equation with two deviating arguments. *Journal of Computational and Applied Mathematics*, **206**(2): 1127-1136.

[15] Eze, E.O and Obasi, U.E (2017): Stability analysis of cubic Duffing Oscillator (The Hard Spring Model). *Transactions of the Nigerian Association of Mathematical Physics*. **3**:45-54.

[16] Bildik N. and Deniz S. (2015), On the asymptotic stability of some particular differential equations. *International Journal of Applied Physics and Mathematics*, **5**(4): 252-258.

[17] Cartwright M.L. (1956), On the stability of solution of certain differential equation of the fourth order. *Journal of Mechanical and Applied Mathematics*, **9**: 185-194.

IJSER